



SGM4812

132mW Differential Input, Stereo Audio Power Amplifier

GENERAL DESCRIPTION

The SGM4812 is a stereo audio power amplifier with differential inputs. Operating on a single 5V power supply, it delivers 132mW of continuous RMS power per channel into a 16Ω loads with typically 0.1% THD+N. Amplifier gain is externally configured by means of two resistors per input channel and does not require external compensation.

The SGM4812 is designed to maximize audio performance in portable communication device applications such as mobile phone. The portable application requires audio power amplifier has minimum of external components and can operate from a single 2.7V to 5.5V power supply.

The SGM4812 features an externally controlled, active-high, micro-power consumption shutdown mode. Additionally, the SGM4812 features an internal thermal shutdown and short circuit protection mechanism.

The SGM4812 is available in Green MSOP-10 package. It operates over an ambient temperature range of -40°C to +85°C.

FEATURES

- Dual Channel, Differential Inputs
- 132mW into 16Ω Load from 5V Power Supply at THD+N = 0.1% (Typical, per Channel)
- 82mW into 32Ω Load from 5V Power Supply at THD+N = 0.1% (Typical, per Channel)
- 2.7V to 5.5V Operation
- Thermal Shutdown and Short Circuit Protection
- Internal Pop Reduction Circuitry
- Internal Mid-Rail Generation
- Low Shutdown Current: 0.36μA (TYP) at 5V
- Shutdown Pin is Compatible with 1.8V Logic
- -40°C to +85°C Operating Temperature Range
- Available in Green MSOP-10 Package

APPLICATIONS

Portable Electronic Systems
Notebook Computers
Mobile Phones
PDAs
GPS



PACKAGE/ORDERING INFORMATION

MODEL	ORDER NUMBER	PACKAGE DESCRIPTION	PACKAGE OPTION	MARKING INFORMATION
SGM4812	SGM4812YMS10/TR	MSOP-10	Tape and Reel, 3000	SGM4812YMS10

ABSOLUTE MAXIMUM RATINGS

Supply Voltage.....	6V
Input Voltage.....	-0.3V to (V ₊) + 0.3V
Storage Temperature Range.....	-65°C to +150°C
Junction Temperature.....	150°C
Operating Temperature Range.....	-40°C to +85°C
Lead Temperature Range (Soldering 10sec)	260°C
ESD Susceptibility	
HBM.....	4000V
MM.....	400V


NOTE:
Stresses beyond those listed under “Absolute Maximum Ratings” may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

CAUTION

This integrated circuit can be damaged by ESD if you don’t pay attention to ESD protection. SGMICRO recommends that all integrated circuits be handled with appropriate precautions. Failure to observe proper handling and installation procedures can cause damage. ESD damage can range from subtle performance degradation to complete device failure. Precision integrated circuits may be more susceptible to damage because very small parametric changes could cause the device not to meet its published specifications.

SGMICRO reserves the right to make any change in circuit design, specification or other related things if necessary without notice at any time. Please contact SGMICRO sales office to get the latest datasheet.

PIN CONFIGURATION (TOP VIEW)




ELECTRICAL CHARACTERISTICS

(T_A = +25°C, unless otherwise specified.)


PARAMETER	SYMBOL	CONDITIONS			MIN	TYP	MAX	UNITS
Supply Voltage	V ₊				2.7		5.5	V
Shutdown Current	I _{SD}	V _{IN} = 0V, V _{SHDN} = V ₊	V ₊ = 5V			0.36	2	μA
			V ₊ = 3.3V			0.13	2	
			V ₊ = 2.7V			0.07		
Output Offset Voltage	V _{OS}	V _{IN} = 0V			-15	2	15	mV
Quiescent Power Supply Current	I _Q	V _{IN} = 0V, I _O = 0A	V ₊ = 5V			1.86	2.6	mA
			V ₊ = 3.3V			1.58	2.5	
			V ₊ = 2.7V			1.50		
Shutdown Voltage Input High	V _{SDIH}				1.8			V
Shutdown Voltage Input Low	V _{SDIL}						0.4	
Power Supply Rejection Ratio	PSRR	V ₊ = 3.2V to 3.4V				74		dB
		V ₊ = 4.9V to 5.1V				70		
Output Power (per Channel)	P _O	f = 1kHz, THD+N = 0.1%	V ₊ = 5V	R _L = 16Ω		132		mW
				R _L = 32Ω		82		
			V ₊ = 3.3V	R _L = 16Ω		46		
				R _L = 32Ω		34		
			V ₊ = 3.0V	R _L = 16Ω		34		
				R _L = 32Ω		27		
			V ₊ = 2.7V	R _L = 16Ω		22		
				R _L = 32Ω		21		
Total Harmonic Distortion + Noise	THD+N	P _O = 60mW, V ₊ = 5V, R _L = 32Ω, f = 20Hz to 20kHz				0.07		%
Power Supply Rejection Ratio	PSRR	f = 217Hz, R _L = 32Ω, Input grounded with 10Ω, (C _{BYPASS} = 0.47μF)	V ₊ = 5V			-55		dB
			V ₊ = 3.3V			-55		
			V ₊ = 3.0V			-55		
			V ₊ = 2.7V			-55		
		f = 1kHz, R _L = 32Ω, Input grounded with 10Ω, (C _{BYPASS} = 0.47μF)	V ₊ = 5V			-71		
			V ₊ = 3.3V			-71		
			V ₊ = 3.0V			-71		
			V ₊ = 2.7V			-71		
Wake-Up Time	T _{WU}	V ₊ = 5V, C _{BYPASS} = 0.47μF				1.8		s
Signal-to-Noise Ratio	SNR	V ₊ = 5V, R _L = 32Ω, P _O = 60mW, BW < 80kHz				-96		dB
Crosstalk	X _{TALK}	V ₊ = 5V, R _L = 32Ω, P _O = 60mW, f = 1kHz				-75		dB

TYPICAL PERFORMANCE CHARACTERISTICS


Small Signal Step Response




Small Signal Step Response




THD+N vs. Frequency




THD+N vs. Frequency



THD+N vs. Frequency




THD+N vs. Frequency




TYPICAL PERFORMANCE CHARACTERISTICS


Small Signal Frequency Response




Small Signal Frequency Response




Small Signal Frequency Response




Small Signal Frequency Response









THD+N vs. Output Power per Channel






THD+N vs. Output Power per Channel




TYPICAL PERFORMANCE CHARACTERISTICS



TYPICAL PERFORMANCE CHARACTERISTICS



TYPICAL APPLICATION




NOTE:

1. A 10kΩ resistor must be serially connected to SHDN pin.

PACKAGE OUTLINE DIMENSIONS

MSOP-10




RECOMMENDED LAND PATTERN (Unit: mm)


Symbol	Dimensions In Millimeters		Dimensions In Inches	
	MIN	MAX	MIN	MAX
A	0.820	1.100	0.032	0.043
A1	0.020	0.150	0.001	0.006
A2	0.750	0.950	0.030	0.037
b	0.180	0.280	0.007	0.011
c	0.090	0.230	0.004	0.009
D	2.900	3.100	0.114	0.122
E	2.900	3.100	0.114	0.122
E1	4.750	5.050	0.187	0.199
e	0.500 BSC		0.020 BSC	
L	0.400	0.800	0.016	0.031
θ	0°	6°	0°	6°

TAPE AND REEL INFORMATION

REEL DIMENSIONS



TAPE DIMENSIONS




NOTE: The picture is only for reference. Please make the object as the standard.

KEY PARAMETER LIST OF TAPE AND REEL

Package Type	Reel Diameter	Reel Width W1 (mm)	A0 (mm)	B0 (mm)	K0 (mm)	P0 (mm)	P1 (mm)	P2 (mm)	W (mm)	Pin1 Quadrant
MSOP-10	13"	12.4	5.2	3.3	1.2	4.0	8.0	2.0	12.0	Q1

CARTON BOX DIMENSIONS



NOTE: The picture is only for reference. Please make the object as the standard.

KEY PARAMETER LIST OF CARTON BOX

Reel Type	Length (mm)	Width (mm)	Height (mm)	Pizza/Carton
13"	386	280	370	5